



CONFIGURATIONS	Phaser 6360N	Phaser 6360DN	Phaser 6360DT	Phaser 6360DX
Speed	Up to 40 ppm colour / 40 ppm black and white			
Duty Cycle	100,000 pages / month*			
Paper Handling	Tray 1 (MPT): 150 sheets; Selectable sizes: 89 x 140 mm to 216 x 914 mm			
Paper input	Standard Tray 2: 550 sheets; Selectable sizes: Up to A4			
Additional 550-sheet Feeder	Optional		Standard	Optional
Additional 1100-sheet Feeder	Optional			Standard
Paper output	250 sheets			
Two-sided output	Optional	Standard		
Print	As fast as 9 seconds colour			
First-page-out time	As fast as 9 seconds colour			
Resolution (max)	2400 x 600 dpi			
Processor	1 GHz			
Memory (std / max)	256 MB / 1 GB		512 MB / 1 GB	
Connectivity	10/100Base-TX Ethernet, USB 2.0, IP v6 **			
Page Description Languages	Adobe® PostScript® 3™, PCL® 5c emulation			
Print features	Booklet printing, Mirror image, Scaling, Watermarks, Custom-size pages, Run Black, Covers, Separators, Ram collation, Remote Printing, N-up			
Productivity kit	Optional			Hard drive: Secure/Proof/Personal/ Shared Saved/Personal Saved Print, Print With, Hard disk collation, PDF-direct print, Extended font/form storage
Security	802.1x, IP sec, SMNP v3, Secure Print and Hard Drive Overwrite (requires Productivity Kit)			
Warranty	One-year on-site warranty***			

*Print volume uniformly distributed over 30 days.

**Requires system firmware version 1.3.7.P.

***Products purchased under a "PagePack" agreement do not carry a warranty. Please refer to your service agreement for full details of your enhanced service package.

Device Management

CentreWare® IS Embedded Web Server, CentreWare Web, Xerox NDPS Gateway, Xerox Usage Analysis Tool, Xerox Support Centre, Configuration card, PrintingScout™, MailLinX email alerts, PhaserSMART®

Print Drivers

Windows® 2000/XP/2003 Server, Vista™, Mac OS® 9.x/X version 10.2 and higher, Novell NetWare® 5.x/6.5 (NPDS only), Linux Red Hat®, Fedora™ Core 5, SUSE™ Linux 10.0, UNIX: Sun Solaris™ 9/10, IBM AIX® 5.1, HP/UX® 11.0/11i, Xerox Walk-Up® Printer Drivers with Windows 2000 or higher

Security

802.1x protocol (EAP-MD5, EAP-TLS, EAP-PEAPv0-MSCHAPv2)

Font Support

PostScript® Fonts: 139; PCL® Fonts: 81

Media Handling

Tray 1 (MPT): 65–216 gsm
Trays 2–5: 65–163 gsm
Two-sided output: 65–163 gsm
Media types: Plain paper, glossy, envelopes, labels, transparencies, card stock

Colour Standards

PANTONE® Colour approved solid-colour simulations, Adobe® PostScript® device-independent colour, CIE International colour standards, Colour options, ICC Profile, Apple ColorSync®

Operating Environment

Temperature: Storage: 0° to 35° C, Operating: 10° to 32° C
Humidity: 15% to 85%
Sound pressure: Printing: 58.0 dB(A), Standby: 34.4 dB(A)
Sound power: Printing: 7.26 B, Standby: 5.0 B
Warm-up time (from sleep mode): 49 seconds

Electrical

Power: 220–240 VAC, 50/60 Hz
Power consumption: 110–127 VAC: Standby: less than 105 W, Printing: less than 750 W, Power save: less than 20 W, 220–240 VAC: Standby: less than 95 W, Printing: less than 750 W, Power save: less than 22 W, 6360DN/DT/DX: ENERGY STAR® qualified
Dimensions (WxDxH)
6360N/DN: 429 x 580 x 513 mm
6360DT: 429 x 580 x 643 mm
6360DX: 572 x 698 x 854 mm
Weight: 6360N/DN: 35.2 kg, 6360DT: 42 kg, 6360DX: 56.2 kg

Certifications

FCC Part 15, Class A, Listed UL 60950-1/CSA 60950-1-03, CE Mark applicable to Directives 73/23/EEC, 89/336/EEC, and 1999/5/EC, Section 508 ADA

Supplies

Standard-capacity toner cartridge:
Black: 9,000 pages¹ 106R01217
Cyan: 5,000 pages¹ 106R01214
Magenta: 5,000 pages¹ 106R01215
Yellow: 5,000 pages¹ 106R01216
High-capacity toner cartridge:
Black: 18,000 pages¹ 106R01221
Cyan: 12,000 pages¹ 106R01218
Magenta: 12,000 pages¹ 106R01219
Yellow: 12,000 pages¹ 106R01220

Routine Maintenance Items

Imaging unit: 35,000 pages² 108R00645
220V Fuser: 100,000 pages³ 115R00056
Transfer roller: 35,000 pages³ 108R00646

Options

N to DN Upgrade 097S03791
Productivity kit 097S03747
550-sheet feeder 097S03378
1100-sheet feeder 097S03379
256 MB memory 097S03381
512 MB memory 097S03382
Wireless network adapter
- Euro power converter 097S03741
- UK power converter 097S03742



Call today. For more information, call or visit us at www.xerox.com/office

¹Average standard pages. Declared yield based on 5% area coverage on a A4-size page. Yield will vary based on image, area coverage and print mode.

²Approximate pages. Declared yield based on an average job size of 4 pages A4-size. Yield will vary depending on job run length and media size and orientation.

³Approximate pages. Declared yield based on A4-size 75 gsm pages. Yield will vary depending on media type, size, weight, orientation, and usage patterns.

Copyright © 2007 XEROX CORPORATION. All rights reserved. Contents of this publication may not be reproduced in any form without permission of XEROX CORPORATION. XEROX®, Phaser® PhaserSmart™, CentreWare® and PrintingScout™ are trademarks of XEROX CORPORATION in the U.S. and/or other countries. Total Satisfaction Services is a service mark of XEROX CORPORATION. All other trademarks are the property of their respective manufacturers. PANTONE Colours generated may not match PANTONE-identified standards. Consult current PANTONE publications for accurate colour. PANTONE, and other Pantone, Inc. trademarks are the property of Pantone, Inc. PCL® is a registered trademark of Hewlett-Packard. As an ENERGY STAR partner, XEROX CORPORATION has determined that these products (Phaser 6360DN / DT / DX) meet the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. The information in this brochure is subject to change without notice. 12/08 6360R-01EB