

# Phaser® 3250

## Black and white laser printer



	Phaser® 3250D	Phaser® 3250DN
<b>Speed</b>	Up to 28 ppm	
<b>Duty Cycle</b>	Up to 30,000 pages / month	
<b>Paper Handling</b>	<b>Bypass Tray:</b> 1 sheet; Custom sizes: 76 x 127 mm to 216 x 356 mm	
	Standard	<b>Tray 1:</b> 250 sheets; Sizes: A6 – A4
Paper input	Optional	<b>Tray 2:</b> 250 sheets; Sizes: A6 – A4
Paper output	150 sheets	
Automatic two-sided output	Standard	
<b>Print</b>	As fast as 8.5 seconds	
First-page-out-time	600 x 600 dpi (up to 1200 x 1200 enhanced image quality)	
Resolution	400 MHz	
Processor	32 MB / 160 MB	
Memory (std/max)	USB 2.0	10/100Base-TX Ethernet, USB 2.0
Connectivity	PCL® 6 and 5e emulations, IBM Pro Printer emulation, Epson emulation, GDI	PostScript® 3™ compatibility, PCL® 6 and 5e emulations, IBM ProPrinter emulation, Epson emulation, GDI
Language support	Watermarks, Poster printing, N-up, Fit to page, Scaling, Overlays, Booklets, Reduce/enlarge, Toner saver, Custom-size pages	
Print features	One-year on-site warranty. Plus optional service extensions available.	
<b>Warranty</b>		

### Device Management

Printer Setting Utility for Windows, 3250DN adds: CentreWare® Internet Services, SNMP 1-2, Ethernal, HTTP, TCP/IP (DN configuration)

### Print Drivers

Windows® 2000/XP/2003 Server, Vista, Mac OS®X version 10.3-10.5, Various Linux® OS including SUSE™ 8.2-9.2, Red Hat® 8-9, Fedora™ Core 1-4, Mandrake 9.2-10.1

### Font Support

1 bitmap, 45 scaleable, 136 PostScript® fonts

### Media Handling

Multipurpose Tray: 60 – 163 gsm  
Media types: Plain paper, envelopes, transparencies, labels, card stock  
Tray 1 and Tray 2 (optional): 60 – 105 gsm  
Media types: Plain paper  
Two sided printing: 75 – 90 gsm

### Operating Environment

Temperature: Storage: 0° to 35° C  
Operating: 10° to 32° C  
Humidity: 20% to 80%  
Sound pressure levels:  
Printing: 54 dB(A)  
Standby: 29 dB(A)  
Warm-up time (from sleep mode): Less than 15 seconds

### Electrical

Power: 220–240 VAC, 50/60 Hz  
Power consumption: Standby: 70 W  
Printing: 400 W  
Power save: 11 W  
ENERGY STAR® qualified

### Dimensions (WxDxH)

364 x 370 x 239 mm  
Weight: 11.9 kg  
Optional 250-sheet Tray 2: 364 x 400 x 86 mm  
Weight: 3.67 kg  
Package Dimensions (WxDxH): 562 x 472 x 344 mm

### Certifications

Listed UL 60950/CSA C22.2 No. 60950, CE Mark applicable to Directives 2006/95/EC and 2004/108/EC

### What Comes In The Box

- Phaser 3250 Printer
- Print Cartridge (2,000 print capacity<sup>1</sup>)
- Software and Documentation CD (with User Manual, Quick Installation Guide, Warranty Statement, Registration Card)
- Power cord
- USB cable



Phaser 3250 shown with optional Tray 2

### Supplies

Standard-Capacity Print Cartridge <sup>1</sup> : 3,500 std. pages	106R01373
High-Capacity Print Cartridge <sup>1</sup> : 5,000 std. pages	106R01374

<sup>1</sup> Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and print mode.

### Options

250-sheet Tray	098N02194
128 MB Phaser Memory	098N02195

### Supplies Recycling Program

Consumables for the Phaser 3250 are part of the Xerox Green World Alliance Supplies Recycling Program. For more information, please visit the Green World Alliance website at [www.xerox.com/gwa](http://www.xerox.com/gwa)

