

Phaser® 6280

Colour Laser Printer



	6280N	6280DN
Speed	Up to 25 ppm colour / 30 ppm black and white (A4)	
Duty Cycle	Up to 70,000 pages / month	
Paper Handling Paper input	Standard	Multipurpose Tray: 150 sheets; Custom sizes: 76.2 x 127 mm to 216 x 356 mm
		Tray 1: 250 sheets; Custom sizes: 148 x 210 mm to 216 x 356 mm (A6-A4)
	Optional	Tray 2: 550 sheets; Custom sizes: 148 x 210 mm to 216 x 356 mm (A6-A4)
Paper output	300 sheets	
Automatic two-sided printing	Optional	Standard
Print First-page-out-time	As fast as 10 seconds	
Resolution (max)	Up to 600 x 600 x 4 dpi	
Processor	400 MHz	
Memory (std / max)	256 MB / 1,280 MB	
Connectivity	USB 2.0, 10/100 Base-TX Ethernet, Optional wireless network adaptor	
Page description languages	PCL® 6, PCL® 5e, Adobe® PostScript® 3™	
Print features	Standard	N-up, Fit to page, Booklet printing, Skip blank pages, Transparency separators, Run black, Covers/Separators*, Poster printing*, Watermarks*, Overlays*, Banner sheets*, Draft mode*
	Optional	Productivity Kit (includes 40 GB hard drive) enables secure / proof / personal / saved print, Hard disk collation, Extended font / form storage
Security	IPv6, IP Sec, SNMPv3, IP Filtering, HTTPS/SSL, 802.1x, Secure Print** (with additional hard drive option), password protected administrative settings	
Warranty	One-year on-site warranty† Plus optional service extensions available	

* Accessed via PCL Driver

** Requires optional memory or hard drive

† Products purchased under a 'PagePack' agreement do not carry a warranty. Please refer to your service agreement for full details of your enhanced service package.

Device Management

Phaser Installer, CentreWare® IS Embedded Web Server, CentreWare Web, PrintingScout™, Email alerts

Print Drivers

Windows® 2000/XP/Vista, Server 2003/2008, Xerox Global Print Driver, Xerox Mobile Express Driver, Mac OS® version 10.3 and above, Linux: SUSE™, Red Hat®, TurboLinux 10 Desktop

Font Capability

136 PostScript® fonts; 81 PCL® fonts

Media Handling

Multipurpose Tray, Tray 2, Tray 3 (optional): 65 – 220 gsm

Media types: Plain paper, glossy, envelopes, labels, transparencies, cardstock, postcards, Two sided printing: 65 – 163 gsm

Colour Standards

PANTONE® Colour approved solid-colour simulations, Colour Correction, ICC Profile, Colour Sync

Operating Environment

Temperature: Storage: -20° to 40° C

Operating: 10° to 32° C

Humidity: 5% to 85%

Sound pressure levels:

Printing: 51.4 dB(A)

Standby: 30.1 dB(A)

Sound power levels:

Printing: 6.33 B, Standby: 4 B

Warm-up time (from sleep mode): 30 seconds

Electrical

Power: 220–240 VAC, 50/60 Hz

Power consumption:

Standby: 70 W

Printing: 450 W

Power save: 4.3 W

ENERGY STAR® qualified

Dimensions (WxDxH)

6280N: 400 x 490 x 473 mm

Weight: 24.5 kg

Package Dimensions (WxDxH):

560 x 650 x 600 mm

Weight: 29.7 kg

6280DN: 400 x 490 x 473 mm

Weight: 29.25 kg

Optional 550-sheet Tray 2: 364 x 400 x 86 mm

Certifications

FCC Part 15, Class B, Listed UL 60950-1/CSA 60950-1-03, CE Mark applicable to Directives 2006/95/EC and 2004/108/EC, Section 508 ADA

What comes in the box

- Phaser 6280 Printer
- Print Cartridge (2,200 (CMY) print capacity¹, (3,000 (K) print capacity¹)
- Software and Documentation CD (with User Manual, Quick Installation Guide, Registration Card, Warranty Statement)
- Power cord

Supplies Recycling Programme

Consumables for the Phaser 6280 are part of the Xerox Green World Alliance Supplies Recycling Programme. For more information, please visit the Green World Alliance website at www.xerox.com/gwa

Supplies

Standard-Capacity Print Cartridge¹:

Black: 3,000 std. pages 106R01391
Cyan: 2,200 std. pages 106R01388
Magenta: 2,200 std. pages 106R01389
Yellow: 2,200 std. pages 106R01390

High-Capacity Print Cartridge¹:

Black: 7,000 std. pages 106R01395
Cyan: 5,900 std. pages 106R01392
Magenta: 5,900 std. pages 106R01393
Yellow: 5,900 std. pages 106R01394

Options

550-sheet feeder 097S03744
550-sheet pedestal stand/feeder 097S03833
256 MB Memory 097S03743
512 MB Memory 097S03635
Duplex unit 097S03746

Productivity Kit (includes 40 GB hard drive) 097S03967
Wireless network adaptor
- European power converter 097S03741
- UK power converter 097S03742

¹ Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

