

Technical specifications

Print technology	Monochrome Laser			
Print speed	A3: Up to 18 ppm. A4: Up to 35 ppm. First page out black: Less than 10 sec			
Processor	460 MHz. MIPS embedded in HP Custom ASIC			
Memory	256 MB. Expandable to 512 MB through one 100-pin DDR DIMM slot. Hard Disk Capacity: Standard, 40 GB			
Print	Quality	HP ProRes 1200, HP FastRes 1200, 600 dpi, 170 lpi		
	Resolution	Up to 1200 x 1200 dpi		
	Printer languages	HP Postscript Level 3 Emulation, PCL 6, PCL 5, PDF 1.4		
	Economical printing	Economode (saves up to 50% toner from 600 dpi), immediate return to Power safe mode after each print job due to Instant-on fuser technology (saves electricity), optional automatic two-sided printing and N-up printing (saves paper)		
	Duty cycle	Up to 200000 pages per month		
	Print margins (mm)	Top: 2 mm. Left: 2 mm. Right: 2 mm. Bottom: 2 mm		
Fax	Telecom compliance	Telecom: TBR-21:1998; EG 201 121:1998, FCC Part 68, Industry Canada CS03, NOM-151-SCTI-1999 (Mexico), PTC-200 (New Zealand), AS/ACIF S002:2001 (Australia), IDA PSTN1 (Singapore), TPS002-01 (Malaysia), IG 0005-11 (Taiwan), HKTA 2011 (Hong Kong), YD514, YD/T589, YD703, GB3382 (China)		
	Fax memory	Dependent on available free disk space		
	Fax resolution	Standard: 200 x 200 dpi. Superfine: 300 x 300 dpi. Photo: 200 x 200 dpi		
Digital sending	File formats	PDF, JPG, TIFF, MTIFF		
	Installation	Via HP Jetdirect embedded networking, HP Jetdirect internal print servers, HP Jetdirect external print servers, HP wireless print servers, and HP connectivity cards		
Scan	Type	Flatbed, ADF. Colour scanning: Yes		
	Scan resolution	Optical: Up to 600 dpi. Enhanced: Up to 1200 dpi		
	Grey scale levels	256		
	Scannable area	Maximum media size: 29.7 x 42.0 cm		
	Margins for scanned items	Left: 5 mm. Top: 6 mm. Right: 5 mm. Bottom: 6 mm		
Copy	Copy speed	Up to 35 cpm		
	Copy resolution	Up to 600 x 600 dpi		
	Multiple copies	Up to 1000		
	Reduce/enlarge	25 to 400%		
Media handling	Input:	Capacity	Weight	Size
	Tray 1	Sheets: 100, envelopes: 10	60 to 199 g/m ²	67.2 x 127 mm postcards, A5, A4, A3, B4, B5, EXE, ITR, LGL, LGR, 76 x 127 mm to 312 x 469.9 mm
	Tray 2	Sheets: 250	60 to 120 g/m ²	A4, B4, B5, ITR, LGL, EXE, A5, 215.9 x 330.2 mm
	Tray 3	Sheets: 250	60 to 120 g/m ²	A4, B4, B5, ITR, LGL, EXE, A5, A3, LGR, 215.9 x 330.2 mm
	ADF	Sheets: 50	60 to 120 g/m ²	
	Output:	Sheets: Up to 250. Envelopes: Up to 25. Transparencies: Up to 200		
Media types	Paper (plain, photo, banner), envelopes, labels, cards (index, greeting), transparencies, letter, pre-punched, recycled			
Interface and connectivity	HP Jetdirect Fast Ethernet embedded print server, Foreign Interface Harness (FIH), USB (compatible with USB 2.0 specifications) type A port, USB (compatible with USB 2.0 specifications) type B port, open EIO slot, optional analog fax. Optional: HP Jetdirect 635n IPv6/IPsec Print Server J7961A, HP Jetdirect 625n Gigabit Ethernet Print Server J7960A, HP Jetdirect 620n Fast Ethernet Print Server J7934A, HP Jetdirect ew2400 802.11g Wireless Print Server J7951A, HP Jetdirect en3700 Fast Ethernet Print Server J7942A, HP Jetdirect 175x Fast Ethernet Print Server J6035D, HP High Performance Serial ATA Hard Disk J7989G, HP 1284B Parallel Card J7972G, HP Jetdirect Connectivity Card J4135A, HP bt450 Bluetooth Wireless Printer and PC Adapter Q6398A, HP bt400 Bluetooth Wireless Printer Adapter Q6399A			
Operating systems compatibility	Windows® 2000, XP Home, XP Professional, XP Professional x64 Edition, Windows® Server 2003; Mac OS 10.2 and higher. Optional: Windows® 2000, XP Home, XP Professional, XP Professional x64 Edition, Windows® Server 2003; Mac OS 10.2 and higher. The latest software and drivers are available for the HP LaserJet M5035 MFP from the HP Website at http://www.hp.com/support/ljm5035mfp			
Network operating systems compatibility	Optional: Windows® 2000, XP Home, XP Professional, XP Professional x64 Edition, Windows® Server 2003; Mac OS 10.2 and higher			
Minimum system requirements	133 MHz processor or higher, 64 MB RAM, 40 MB available hard disk space, USB or network port connection. Mac OS 10.2 and higher, 128 MB RAM, 25 MB available hard disk space, network or USB port			
Standard software	Drivers on the web: Printing system, PCL 6 driver only, PCL 5 driver only, PS driver only, WJA applet, UPD PCL 5, UPD PS, HP Easy Printer Care Software, PC fax driver			
Control panel	4 job control buttons, 13 button numeric keypad, touch screen graphical display, 3 status lights, 1 display contrast knob			
Power	Requirements: Input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 2 Hz), 6 amp. Consumption: 0.1 watts maximum (off), 24 watts maximum (sleep), 280 watts maximum (ready), 600 watts maximum (printing), 1265 watts maximum (copying)			
Dimensions (w x d x h)	Out of package: M5035 MFP: 610 x 571 x 584 mm; M5035x MFP: 743 x 743 x 997 mm; M5035xs MFP: 743 x 743 x 1183 mm. Packaged: M5035 MFP: 766 x 721 x 852 mm; M5035x MFP: 900 x 900 x 1418 mm; M5035xs MFP: 900 x 900 x 1567 mm			
Weight	Out of package: M5035 MFP: 55 kg; M5035x MFP: 93 kg; M5035xs MFP: 97 kg. Packaged: M5035 MFP: 61.1 kg; M5035x MFP: 100 kg; M5035xs MFP: 104.3 kg			

<http://www.hp.com/uk>



© Copyright Hewlett-Packard Development Company, L.P. 2006. The information contained herein is subject to change without notice. The only warranties for HP Products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Published in EMEA 10/06 4AA0-5300EEE

