

	8860N	8860MFP/D
Speed	Up to 30 ppm colour / 30 ppm black and white	
Duty Cycle	120,000 images / month	
Paper Handling	Tray 1: 100 sheets; Custom sizes: 76 x 127 mm to 216 x 356 mm Tray 2: 525 sheets; Selectable sizes: 140 x 216 mm to 216 x 356 mm	
Paper input	standard	
	optional	Tray 3: 525 sheets; Selectable sizes: 140 x 216 mm to 216 x 356 mm Tray 4: 525 sheets; Selectable sizes: 140 x 216 mm to 216 x 356 mm
Document handler	NA	Duplex Automatic Document Feeder: 50 sheets
Paper output	250 sheets	
Two-sided output	Standard	
Copy	As fast as 15 seconds colour / 15 seconds black and white	
First-page-out time	NA	
Resolution (max)	NA	600 x 600 dpi
Copy features	NA	Book copying, Booklet creation, Collation, Covers, Image Centre, Image shift, N-up, Reduce / Enlarge, Repeat image, Colour Password Protection
Print	As fast as 6 seconds colour	
First-page-out time	As fast as 5 seconds colour	
Resolution (max)	Up to 2400 FinePoint™	
Memory (std / max)	256 MB / 1 GB	512 MB / 1 GB
Processor / PDL	750 MHz processor / True Adobe® PostScript® 3™, PCL® 5c emulation	
Connectivity	10/100Base-TX Ethernet, USB 2.0	
Print features	Custom-size pages, Xerox Installer, Intelligent Ready, Booklet printing, Smart Trays, Remote Printing, Job Accounting, Printer Neighbourhood, Run Black	
Productivity kit (with Hard drive)	Optional	Personal/Personal Saved/Secure/Proof/Saved Print, (with Hard drive) Print With, Extended font/form storage, Collation, Hard Drive Overwrite
Scan	Scan to PC / Mac, Scan to TWAIN application, Scan to email via PC, Scan to desktop, Scan to Public / Private Folders	
Scan destinations	NA	
Scan to PC Desktop®	NA	Scan to PC Desktop, Professional Small Business Edition
Fax	33.6 kbps Super Group 3, 200 individual / 100 group Speed dials, fax to multiple addresses, Fax security	
Fax features	NA	
Warranty	One-year on-site warranty	

Device Management

Xerox® CentreWare® Printer Management for Microsoft, Novell and UNIX, Xerox CentreWare® IS Embedded Web Server, CentreWare Web, Xerox NDPS Gateway, Usage Analysis Tool, Configuration card, PrintingScout®, MailInX email alerts, PhaserSMART®

Print Drivers

Windows® 2000/XP/2003 Server, Vista, Mac OS® 9.x/X version 10.2 and higher, Novell NetWare® 5.x/6.5 (NDPS only), UNIX/ Linux (see web), Xerox Walk-Up® Printer Drivers

Security

802.1x protocol (EAP-MD5, EAP-TLS, EAP-PEAP0-MSCHAPv2)

Media Handling

Tray 1: 60 – 220 gsm; Trays 2 – 4: 60 – 120 gsm; Duplex Automatic Document Feeder: 60 – 120 gsm; Media types: transparencies, envelopes, labels, glossy paper, custom-size paper

Operating Environment

Temperature: Nonoperating: -30° to 60° C; Operating: 10° to 32° C; Relative Humidity: Nonoperating: 10% to 95%; Operating: 10% to 80%; Sound power levels: Operating: 54 dBA, Standby: 33 dBA

Electrical

Power: 110 – 240 V, 50 – 60 Hz; Power consumption: Average: 230 W; Max: 1500 W; Energy Star® qualified (S configuration)

Dimensions (WxDxH)

Phaser 8860: 406 x 533.4 x 368 mm; Weight: 28 kg.; Phaser 8860MFP: 532 x 665 x 620 mm; Weight: 43 kg.; Additional feeder: 135 mm; Weight: 7.3 kg.; Optional cart: 500 x 670 x 360 mm

Certifications

Certified to UL 60950-1/CSA 60950-1-03 1st Edition, FCC Part 15 Class A, Low Voltage Directive 73/23/EEC, EN 60950-1, EMC Directive 89/336/EE3, EN55022 Class A, EN 55024, ROHS Directive 2002/95/EC

Supplies

Genuine XEROX® Solid Ink
6 Sticks Cyan: 14,000 pages¹ 108R00746
6 Sticks Magenta: 14,000 pages¹ 108R00747
6 Sticks Yellow: 14,000 pages¹ 108R00748
6 Sticks Black: 14,000 pages¹ 108R00749

Options

Productivity Kit w/ Hard Drive (8860) 097503856
525-Sheet Feeder (8860) 097503667
525-Sheet Feeder (8860MFP) 097503638
256 MB Memory (8860) 097503381
512 MB Memory 097503382
System Cart 097503318
Wireless Network Adapter
– European Power Converter 097503741
– UK Power Converter 097503742
Scan to PC Desktop (8860MFP)
– Professional Small Business Edition (extra licenses) see web for order details: www.xerox.com/office/scantodesktop

Routine Maintenance Items

Drum Maintenance Kit <30,000 pages² 113R00736

¹ Average standard pages. Declared Yield in accordance with ISO/IEC 24711. Yield will vary based on image, area coverage and print mode.

² Approximate pages. Declared Yield based on A4-size 20 lb. (75 gsm) pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.



Call today. For more information, call or visit us at www.xerox.com/office

