

Technical specifications

Print technology	In-line colour laser, direct-to-page printing		
Print speed	Document Type Black/colour A4 Black/colour A3	Plain paper Up to 28 ppm Up to 14 ppm	Transparencies Up to 5.5 ppm
	First page out: 16 sec from "Ready", 41 sec from "Powersave", 120 sec from "Cold start" Exact speed varies depending on the system configuration, software application, driver, and document complexity.		
Processor	533 MHz, MIPS 64 20kc processor		
Memory	Standard: HP Color LaserJet 5550/n/dn printer: 160 MB; HP Color LaserJet 5550dn/hdn printer: 288 MB Expandable to 544 MB through 2 industry-standard 200-pin DDR SODIMM slots using Memory Enhancement technology (ME). 20 GB HP EIO hard disk (standard with the HP Color LaserJet 5550hdn)		
Print resolution	HP Imageret 3600 (high resolution laser imaging system, accurate print mechanism, superior image enhancements, intelligent colour control, adaptive gloss finish, system-optimised for HP High-Gloss Paper, smart printing supplies with chemically-grown spherical toner). Supports colour management systems based on ICC profiles; Apple ColorSync, Microsoft® ICM, Adobe®, Corel®, Quark®, and others. PANTONE® CALIBRATED™ for PANTONE PMS support. Supports SWOP, Euro and DIC press emulations.		
Printer languages	HP PCL 5c, HP PCL 6, HP Postscript Level 3 emulation, PDF 1.3		
Typefaces/fonts	80 internal scalable fonts available to HP PCL and HP Postscript Level 3 emulation		
Duty cycle	Up to 120,000 pages per month		
Print margins (mm)	Top: 5 mm, left: 5 mm, right: 5 mm, bottom: 5 mm		
Media handling	Input Tray 1	Capacity 100 sheets, 60 transparencies, 20 envelopes	Weight 60 to 200 g/m ²
	Output: Tray 2/3/4/5	500 sheets	60 to 120 g/m ²
	Duplex printing: Automatic (standard with the HP Color LaserJet 5550dn/dtn/hdn. HP Color LaserJet 5500/n not upgradeable; manual duplex available) Duplex media sizes: A4, A4-rotated, A3, B4-JIS, B5-JIS Duplex media weights: Up to 120 g/m ²		
Interface and connectivity	Standard: IEEE 1284-C compliant bi-directional parallel port, USB (compatible with USB 1.1 specifications), jetlink. HP Jetdirect 620n internal print server 10/100Base-TX (standard with HP Color LaserJet 5550n/dn/dtn/hdn models), open EIO slot(s): HP CLJ 5550: 3 slots, HP CLJ 5550n/dn/dtn: 2 slots, HP CLJ 5550hdn: 1 slot.		
Operating systems compatibility	Drivers included: Microsoft® Windows® 98, Me, NT, 2000, XP, Server 2003; Macintosh OS 9, OS 10 Driver download: OS/2, UNIX, Linux; basic printing support for DOS. Current software and drivers are available from the Internet.		
Network operating systems compatibility	Via HP Jetdirect print servers: Microsoft® Windows® 98, Me, NT 4.0, 2000, XP, XP 64-Bit, Server 2003; Novell® NetWare 3.2, 4.2, 5.x, 6.x; Apple Mac OS 9.0 and later; Red Hat Linux 6.x and later; SuSE Linux 6.x and later; HP-UX 10.20, 11.x; Solaris™ 2.5x, 2.6, 7, 8, 9, 10 (SPARC systems only); IBM AIX 3.2.5 and later; MPE-iX Compatible network protocols*: with standard HP Jetdirect 620n Fast Ethernet print server: TCP/IP (IP Direct mode, may require software from NOS vendor or third party vendor : LPD, FTP, IPP), IPX/SPX, DLC/LLC, AppleTalk, Auto-IP, Apple Rendezvous compatible, NDS, Bindery, NCP, Telnet, SLP, IGMP, BOOT/DHCP, WINS, SNMP (v1, v2c, v3), HTTP.		
Minimum system requirements	Microsoft® Windows® 98: Pentium® 90 with 16 MB of RAM; Windows Me: Pentium 150 with 32 MB of RAM; Windows NT® 4.0: Pentium 90 with 32 MB of RAM; Windows 2000: 300 MHz Processor with 64 MB of RAM; Windows XP: 233 MHz Processor with 64 MB of RAM; 180 MB free hard disk space for Windows, 160 MB for Mac; Mac OS 9.0, 9.0.4, 9.1, 9.2, 10.1; CD-ROM drive or Internet connection; dedicated IEEE-1284 parallel port Mac OS 9.0, 9.0.4, 9.1, 9.2, 10.1: 4 MB RAM and 160 MB free hard disk space; AppleTalk or USB (compatible with USB 1.1 specifications) connectivity solution		
Control panel	LCD backlit panel display with up to 4 lines of text and animated printer graphics, 3 LED status lights. "Cancel job", "Pause/Resume", "Help" buttons		
Power requirements	Input voltage: 100 to 240 VAC (-10/+6%), 50/60 Hz (±2 Hz) Supply type: Internal: built-in power supply for either 110- or 220-VAC source		
Power consumption	0.3 watts maximum (Off), 28 watts maximum (Powersave), 93 watts maximum (Standby), 632 watts maximum (Printing)		
Dimensions (w x d x h) (out of package/packaged)	HP Color LaserJet 5550/n/dn printer: 577 x 704 x 640 mm/995 x 767 x 822 mm HP Color LaserJet 5550dn printer: 630 x 718 x 833 mm/979 x 797 x 1109 mm HP Color LaserJet 5550hdn printer: 630 x 718 x 1097 mm/979 x 797 x 1359 mm		
Weight (out of package/packaged)	HP Color LaserJet 5550/n/dn printer: 60 kg/85 kg, HP Color LaserJet 5550dn printer: 108 kg/138 kg, HP Color LaserJet 5550hdn printer: 136 kg/168 kg		
Printer management	HP Web Jetadmin, HP Embedded Web Server, HP E-Toolbox		
Operating environment	Environmental ranges: operating temperature: 15 to 27° C, recommended operating temperature: 15 to 27° C; operating humidity: 10 to 70% RH, recommended operating humidity: 30 to 70% RH; storage temperature: 0 to 35° C, storage humidity: 10 to 90% RH. Noise level per ISO 9296: sound power: LwAd: 6.6 B(A) (Printing), 4.9 B(A) (Powersave/Standby), sound pressure: LpAm: 49 dB(A) (Printing), 33 dB(A) (Powersave)		
Certifications	Safety certifications: Regulatory standards: Czech Republic (CSN-IEC 60950-IEC 60825-1), Estonia (EEI-EN60950-IEC 60825-1), EU (CE Mark/Low Voltage Directive 73/23/EEC), Germany (TÜV-EN60950-IEC 60825-1), Hungary (MEEI-IEC 60950-IEC 60825-1), Lithuania (LS-IEC 60950-IEC 60825-1), Poland (B Mark-IEC 60950-IEC60825-1), Russia (GOST-R50377), Slovakia (IEC 60950-IEC60825-1), Slovenia (SQR-IEC 60950-EN60825-1), South Africa (IEC 60950-IEC60825-1). EMC certifications: CISPR 22: 1997/EN 55022: 1998 Class B, EN 61000-32:2000, EN 61000-3-3: 1995, EN 55024: 1998, FCC Title 47 CFR, Part 15 Class B/ICES-003, Issue 4/GB9254-1998, GB17625.1-2003, EMC Directive 89/336/EEC and the Low Voltage Directive 73/23/EEC, and carries the CE-Marking accordingly		
Warranty	1 year, next-day, on-site warranty. Optional HP Care Pack services		

*Not all protocol and operating system combinations are supported. For more information, refer to <http://www.hp.com/go/jetdirect>

Ordering information

Q3713A	HP Color LaserJet 5550 Printer, (IEEE 1284-C parallel cable, 160 MB, tray 1: 100-sheet input tray, tray 2: 500-sheet input tray)
Q3714A	HP Color LaserJet 5550n Printer (as above plus: HP Jetdirect 620n Fast Ethernet print server, excludes IEEE 1284-C parallel cable)
Q3715A	HP Color LaserJet 5550dn Printer (as above plus: automatic built-in duplexer)
Q3716A	HP Color LaserJet 5550dtn Printer (as above plus: tray 3: 500-sheet input tray, printer stand, additional 128 MB)
Q3717A	HP Color LaserJet 5550hdn Printer (as above plus: tray 4/5: 2 x 500-sheet input trays, 20 GB hard disk)

Accessories

C7130B	500-sheet tray and feeder unit
Q9669B	Printer stand
Q2630A	HP 128 MB DDR 200-pin SDRAM DIMM
Q2631A	HP 256 MB DDR 200-pin SDRAM DIMM
Q2632A	HP 512 MB DDR 200-pin SDRAM DIMM
C6073A	HP EIO Hard disk, 20 GB

HP Jetdirect print servers (selection)

J6072A	HP bi1300 Bluetooth Wireless print adapter (for USB 1.1 or parallel)
J7934A	HP Jetdirect 620n internal print server (Fast Ethernet 10/100Base-TX, 802.1x)
J6058A	HP Jetdirect 680n internal print server (802.11b wireless Fast Ethernet)
J7942A	HP Jetdirect en3700 Fast Ethernet external print server (USB 2.0 port)

Cables

C2946A	HP IEEE 1284-compliant bi-directional parallel cable, C-type connector, 3 m
92215N	HP LocalTalk cable kit, 2 m
92215S	HP serial printer cable, 2 m

Supplies

C9730A	HP Color LaserJet Smart Print Cartridge, black (up to 13,000 pages*)
C9731A	HP Color LaserJet Smart Print Cartridge, cyan (up to 12,000 pages*)
C9732A	HP Color LaserJet Smart Print Cartridge, yellow (up to 12,000 pages*)
C9733A	HP Color LaserJet Smart Print Cartridge, magenta (up to 12,000 pages*)

*Based on 5% coverage

Maintenance kits

C9734B	HP Image transfer kit ³
C9735B	HP Image fuser kit (110V) ⁴
C9736B	HP Image fuser kit (220V) ⁴

³Up to 120,000 pages

⁴Up to 150,000 pages

Service & support

H5549A/E	HP Care Pack – Next business day on-site response, 3 years
H2691A/E	HP Care Pack – Same business day on-site response, 3 years
H3184PA/PE	HP Care Pack – Next business day on-site response, 1 year post warranty
U4942PA/PE	HP Care Pack – Same business day on-site response, 1 year post warranty
H2872A/E	Installation & network configuration for 1 network printer

<http://www.hp.com>

For more information, please call your local HP sales office or representative: **Austria:** 0800 242 242, **Algeria:** (0)61 56 45 43, **Bahrain:** 800 728, **Belgium:** (078) 15 20 30 (0.0496 EUR/min), **Bulgaria:** (+359) 2960 1940, **Croatia:** (+385 1) 60 60 200, **Czech Republic:** (00 420 2) 261 108 108 (Prague), **Denmark:** 48 12 10 00, **Egypt:** 532 5222, **Estonia:** (+372) 6813 823, **Finland:** (+358) 0205350 or 0205 350, **France:** (1) 69 82 6060, **Germany:** 0180 532 6222 (12 Cent/min), **Greece:** (01) 678 96 00, **Hungary:** (+36) 1 382-1111, **Iceland:** (354) 570 1000, **Ireland:** + 353 1 6158200, **Israel:** (972) 9 8304848, **Italy:** (02) 92121, **Kazakhstan:** +7 (3272) 980 824, **Latvia:** (371) 800 80 12, **Lithuania:** 8 800 10000 or 8 5 2103333, **Luxembourg:** (+352) 263 160 34, **Middle East:** 00971 4 883 4427, **Morocco (African Region):** +212 22 40 47 47, **Netherlands:** (020) 5476666, **Norway:** 22 735600, **Poland:** infolinia: 0-800 122 622, **Portugal:** (808) 206 001, **Romania:** (+401) 205 3300, **Russia:** +7 (095) 797 35 00, **Saudi Arabia:** 800 124 4646, **Serbia/Montenegro:** +381 11 201 99 00, **Slovakia:** +421-2-50222111, **Slovenia:** +3861 2307 420, **South Africa:** 0800 118 883, **Spain:** (91) 634 88 00, **Sweden:** (08) 444 2000, **Switzerland:** 0848 88 44 66, **Tunisia:** 71 891 222, **Turkey:** +90 (216) 579 71 71, **UAE:** 8004910, **UK:** 08705 474747, **Ukraine:** +380 44 490 61 20.



©2004 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP Products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Published in EMEA 08/04 5982-6714EEE

