

Phaser® 6180MFP

	Phaser 6180MFP/N	Phaser 6180MFP/D
Speed	Up to 20 ppm colour / 30 ppm black and white	
Duty Cycle	60,000 pages / month ¹	
Paper Handling		
Paper input	Standard	Tray 1 (MPT): 150 sheets; Custom sizes: 76.2 x 127 mm to 220 x 355.6 mm
	Optional	Tray 2: 250 sheets; Custom sizes: 148 x 210 mm to 215.9 x 355.6 mm Tray 3 (feeder with stand): 550 sheets; Custom sizes: 148 x 210 mm to 215.9 x 355.6 mm
Document handler	Automatic Document Feeder: 50 sheets; Custom sizes: 148 x 210 mm to 220 x 355.6 mm	
Paper output	300 sheets	
Automatic two-sided printing	Optional	Standard
Copy		
Copy speed	Up to 7 cpm colour / 20 cpm black and white	
First-page-out-time	As fast as 20 seconds colour / 11 seconds black and white	
Resolution (max)	600 x 600 dpi	
Copy features	Collation, Reduce/Enlarge, ID Card Copy, Poster	
Print		
First-page-out-time	As fast as 10 seconds colour / 10 seconds black and white	
Resolution (max)	600 x 600 x 4 dpi	
Processor	400 MHz	
Memory (std / max)	384 MB / 1,408 MB	
Connectivity	10/100Base-TX Ethernet, USB 2.0, Parallel, Optional: multiprotocol network card, wireless network adapter	
Page description languages	PCL® 6 emulation, Adobe® PostScript® 3™	
Print features	Standard	N-up, Booklet printing, Fit to page, Transparency separators, Skip blank pages, Covers/Separators ² , Poster ² , Watermarks ² , Overlays ² , Banner sheets ² , Proof Print, Secure Print, RAM collation
Scan		
Scan destinations	Scan to Computer Application (USB), Scan to Server (FTP), Scan to Computer (using SMB), Scan to Email	
Scan features	JPEG, TIFF, PDF, Colour Scanning, Xerox Scan to PC Desktop® software (optional)	
Fax		
Fax features	Walk-up fax and LAN fax ² (fax from the PCL print driver) (33.6 Kbps with MMR/MR/MH, JBIG, JPEG compression), Junk fax barrier, Memory fax, Secure receive, Delay fax, Colour fax, Speed dials, Group dials	
Warranty	One-year on-site warranty ³	

¹ Print Volume uniformly distributed over 30 days. ² Accessed via PCL driver.

³ Products purchased under a 'PagePack' agreement do not carry a warranty. Please refer to your service agreement for full details of your enhanced service package.

Device Management

CentreWare® IS Embedded Web Server, CentreWare Web, PrintingScout™, email alerts

Print Drivers

Windows® 2000/2003 Server/XP Pro/XP Vista, Mac OS® X version 10.2 or higher, Solaris 8/9/10, HP-UX® 11.0, AIX® 4.3.3, Turbo Linux™ 10 Desktop, RedHat® ES3/ES4, SUSE™ 9.2/9.3, Fedora™ Core 1, YellowDog 3.x

Font Capability

PostScript® fonts: 136; PCL® fonts: 81

Media Handling

All trays: 65 – 220 gsm; Two-sided output: 65 – 163 gsm; Automatic Document Feeder: 65 – 120 gsm; Media types: Plain paper, envelopes, labels, transparencies, card stock, glossy coated

Colour Standards

PANTONE® Colour approved solid-colour Simulations, Colour Correction, ICC Profile

Operating Environment

Temperature: Operating: 10° to 32° C; Storage: 0° to 35° C; Relative humidity: 15 to 80 %; Sound pressure: Operating: 51.6dBA, Standby: 26.8dBA; Sound power level: Operating: 6.59B; Standby: 4.18B

Electrical

Power: 220–240 VAC, 50/60 Hz; Power consumption: Standby: 90 W, Printing: 500 W, Power Save: 17 W; ENERGY STAR® qualified

Dimensions (WxDxH)

460 x 520 x 730 mm; Weight: 6180MFP/N: 40 kg, 6180MFP/D: 41 kg

Certifications

FCC Part 15, Class B, FCC Part 68, Listed UL 60950-1/CSA 60950-1-03, CE Mark applicable to Directives 73/23/EEC, 89/336/EEC, and 1999/5/EC, RoHS Directive 2002/ 95/EC, WEEE Directive 2002/96/EC

Supplies

Standard-capacity print cartridge*:

Black: 3,000 pages 113R00722
Cyan: 2,000 pages 113R00719
Magenta: 2,000 pages 113R00720
Yellow: 2,000 pages 113R00721

High-capacity print cartridge*:

Black: 8,000 pages 113R00726
Cyan: 6,000 pages 113R00723
Magenta: 6,000 pages 113R00724
Yellow: 6,000 pages 113R00725

Options

550-sheet feeder and stand 097503833
256 MB Memory 097503743
512 MB Memory 097503635
Automatic two-sided printing unit 097503746
Scan to PC Desktop:
Professional Small Business Edition 301K19560
SE Small Business Edition 301K19540
Multi-Protocol Network Card 097503745
(Support for DDNS, IPP, Wins, SSL/HTTPS, IPv6, IPsec, WSD-Print)
Wireless Network Adaptor
European power converter 097503741
UK power converter 097503742

*Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.



© 2008 Xerox Corporation. All rights reserved. Contents of this publication may not be reproduced in any form without permission of Xerox Corporation. XEROX®, Phaser®, CentreWare®, Scan to PC Desktop® and the sphere of connectivity design are trademarks of Xerox Corporation in the U.S. and/or other countries. Total Satisfaction Services is a service mark of Xerox Corporation. All other trademarks are the property of their respective manufacturers. PANTONE Colours generated may not match PANTONE-identified standards. Consult current PANTONE publications for accurate colour. PANTONE®, and other Pantone, Inc. trademarks are the property of Pantone, Inc. As an Energy Star partner, Xerox Corporation has determined that this product meets the Energy Star guidelines for energy efficiency. Energy Star and the Energy Star mark are registered U.S. marks. The information in this brochure is subject to change without notice. 11/08

Call today. For more information call or visit us at www.xerox.com/office

61CBR-01EC